



Aerial Work Platforms Reaching New Heights with Greener Insights



Guangxi LiuGong Machinery Co., Ltd.
No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China
T: +86 772 388 6124 E: overseas@liugong.com
www.liugong.com

Like and follow us:



LG AWP product line EN 012025

The LiuGong series of logos herein, including but not limited to word marks, device marks, letter of alphabet marks and combination marks, as the registered trademarks of Guangxi LiuGong Group Co., Ltd. are used by Guangxi LiuGong Machinery Co., Ltd. with legal permission, and shall not be used without permission. Specifications and designs are subject to change without notice. Illustrations and pictures may include optional equipment and may not include all standard equipment. Equipment and options varies by regional availability.

TOUGH WORLD. TOUGH EQUIPMENT.

Electric Drive Scissor Lifts



Parameter	LS0407EM	LS0507EM	LS0607E/A	LS0808E	LS0812E	LS1012E	LS1212E	LS1412E	LS1414E
Max. Working Height /m	5.6	6.5	7.8	10/8	10	12	14/9.5	15.7/8	16/8
Load Capacity /kg (Extended Platform/kg)	240(110)	240(110)	230(113)	230(100)	450(120)	350(120)	320(120)	250(113)	350(136)
Platform Size /m	1.3×0.72	1.3×0.72	1.64×0.75	2.28×0.81	2.28×1.15	2.28×1.15	2.28×1.15	2.64×1.15	2.88×1.35
Overall Length /m	1.39	1.413	1.86	2.48	2.48	2.48	2.48	2.84	3.1
Overall Width /m	0.76	0.76	0.785	0.844	1.19	1.19	1.19	1.25	1.38
Weight /kg	860	895	1540	2200	2480	2780	2980	3300	3720
Battery (Standard: Lead-Acid)	24V/100Ah	24V/100Ah	24V/225Ah	24V/225Ah	24V/225Ah	24V/225Ah	24V/225Ah	24V/270Ah	24V/270Ah

Electric Drive Scissor Lifts-c series



Parameter	LS0507EM-c	LS0608E-c	LS0808E-c	LS0812E-c	LS1012E-c	LS1212E-c	LS1412E-c	LS1414E-c
Max. Working Height /m	6.5	7.8	10/8	10	11.8	13.8/9.5	15.7/8	16/8
Load Capacity /kg (Extended Platform/kg)	240(110)	230(113)	230(100)	450(120)	350(120)	320(120)	250(113)	350(136)
Overall Length /m	1.39	1.86	2.49	2.49	2.49	2.49	2.84	3.1
Overall Width /m	0.76	0.81	0.84	1.19	1.18	1.19	1.25	1.38
Weight /kg	970	1370	2200	2400	2440	2760	3300	3800
Battery (Standard: Lead-Acid)	24V/100Ah	24V/135Ah	24V/225Ah	24V/225Ah	24V/225Ah	24V/225Ah	24V/270Ah	24V/270Ah

Hydraulic Drive Scissor Lifts



Parameter	LS0507HM	LS0607H	LS0808H	LS0812H	LS1012H	LS1212H	LS1412H	LS1414H
Max. Working Height /m	6.5	7.8	10/8	10	12	14/9.5	15.7/8	16/8
Load Capacity /kg (Extended Platform/kg)	240(110)	230(113)	230(100)	450(120)	350(120)	320(120)	250(113)	350(136)
Platform Size /m	1.3×0.72	1.64×0.75	2.28×0.81	2.28×1.15	2.28×1.15	2.28×1.15	2.64×1.15	2.88×1.35
Overall Length /m	1.49	1.86	2.48	2.48	2.48	2.48	2.84	3.1
Overall Width /m	0.76	0.785	0.844	1.19	1.19	1.19	1.25	1.38
Weight /kg	950	1520	2180	2460	2760	2960	3280	3700
Battery (Standard: Lead-Acid)	24V/100Ah	24V/225Ah	24V/225Ah	24V/225Ah	24V/225Ah	24V/225Ah	24V/270Ah	24V/270Ah

Hydraulic Drive Scissor Lifts-c series




Parameter	LS0507HM-c	LS0608H-c	LS0808H-c	LS0809H-c	LS1012H-c	LS1212H-c	LS1412H-c	LS1414H-c
Max. Working Height /m	6.5	7.8	10	10	11.8	13.8/9.5	15.7/8	16/8
Load Capacity /kg (Extended Platform/kg)	240(110)	230(113)	230(100)	230(100)	350(120)	320(120)	250(113)	350(136)
Overall Length /m	1.49	1.86	2.48	2.48	2.48	2.48	2.84	3.1
Overall Width /m	0.76	0.81	0.84	0.93	1.18	1.18	1.25	1.38
Weight /kg	950	1350	2180	2200	2420	2740	3280	3780
Battery (Standard: Lead-Acid)	24V/100Ah	24V/135Ah	24V/225Ah	24V/225Ah	24V/225Ah	24V/225Ah	24V/270Ah	24V/270Ah

Crawler Scissor Lift



Parameter	LS0610EC	LS1216HC
Max. Working Height /m	7.8	14
Load Capacity /kg (Extended Platform/kg)	230(120)	320(120)
Overall Length /m	2.13	2.8
Overall Width /m	1.01	1.56
Weight /kg	1830 1740	3700
Battery (Standard: Lead-Acid)	24V/225Ah	48V/225Ah

Rough Terrain Scissor Lift



Parameter	LS1623ERT
Max. Working Height /m	18
Load Capacity /kg (Extended Platform/kg)	680(227)
Overall Length /m	4.88
Overall Width /m	2.29
Weight /kg	8800
Battery (Standard: Lead-Acid)	48V/450Ah

Electric Telescopic Boom Lifts



Parameter	LT16JE	LT18JE	LT20JE	LT22JE	LT26JE	LT30JE	LT32JE
Max. Working Height /m	18.2	20.5	21.5	23.8	28.1	31.6	34
Max. Horizontal Reach /m	11.3	12	13.4	15.7	19.88	19.3	21.2
Load Capacity /kg	300	350	320	300/454	300/454	300/454	300/454
Overall Width /m	2.3	2.42	2.42	2.42	2.44	2.49	2.49
Weight /kg	7300	8250	9500	11070	15000	17400	18950
Battery(Lithum)	51.2V/304Ah	48V/375Ah	48V/460Ah	48V/460Ah	83.2V/460Ah	83.2V/460Ah	83.72V/460Ah

Electric Telescopic Boom Lifts-c series



Parameter	LT16JE-c	LT18JE-c	LT20JE-c	LT22JE-c	LT26JE-c	LT30JE-c
Max. Working Height /m	18.2	20.5	22	23.8	28.1	31.6
Max. Horizontal Reach /m	11.3	12	13.4	15.7	17.5	18.7
Load Capacity /kg	300	350	320	300/454	300/454	300/454
Overall Width /m	2.3	2.42	2.42	2.42	2.49	2.49
Weight /kg	7500	8250	9250	11600	12880	17400
Battery(Lithum)	51.2V/304Ah	48V/375Ah	48V/375Ah	48V/460Ah	83.2V/350Ah	83.2V/460Ah

Diesel Telescopic Boom Lifts



Parameter	LT20J/LT20JG4	LT28J/LT28JG4	LT32JG4
Max. Working Height /m	22	30	34
Max. Horizontal Reach /m	17.2	22.3	20.3
Load Capacity /kg	300/454	300/454	300/454
Overall Width /m	2.49	2.49	2.49
Weight /kg	12500	18900	19680
Power	Yuchai YCF3050-T307/36.5kW YCF3050-T423/36.8KW	Yuchai YCF3075-T302/55.8kW YCF3075-T480/55KW	Yuchai YCF3075-T480/55KW

Electric Articulated Boom Lifts



Parameter	LA14JE	LA16JE	LA16JE-c	LA20JE
Max. Working Height /m	16	17.8	17.8	22.2
Maximum Horizontal Reach /m	8.35	9.78	9.78	13.2
Maximum Crossing Height /m	7.8	8.16	8.16	8.3
Rated Load /kg	260	260	260	260
Overall Width /m	1.85	2.3	2.3	2.42
Weight /kg	6980	7300	7600	9500
Battery (Lithium battery)	51.2V/304Ah Optional lead-acid battery 48V/300Ah	51.2V/304Ah	51.2V/304Ah	48V/460Ah

Vertical Mast Lift



Parameter	LM09JE
Max. Working Height /m	11.2(indoor) /10.1(outdoor)
Maximum Horizontal Reach /m	3.6
Maximum Crossing Height /m	7.75
Rated Load /kg	200
Overall Width /m	1
Weight /kg	2990
Battery (Lithium battery)	225Ah

Diesel Telescopic Handler



Parameter	LTH0735A
Max. Lift Height /m	6.95
Max. Overall Lift Capacity /kg	3500
Max. Horizontal Reach /m	3.95
Operating Weight /kg	7850
Max. Drive Speed /km/h	40
Max. Traction Force /kN	85